



714Strip

Description

Dedicated blanket for strippable and varnishing applications.


Easy to strip due to the special compressible layer.

Suitable for spot coating applications.


MAIN APPLICATION

Commercial Sheetfed, Packaging

Vulcan 714Strip is available in 4-ply, (1,96 mm) thickness.



Standard



Vulcan 714Strip



The product at a glance

PRINTING SURFACE COLOUR	Blue
THICKNESS (mm)	1,96
SURFACE ROUGHNESS (Ra micron)	0,6
INK COMPATIBILITY	Conventional
ELONGATION (%)	<0,9
TENSILE STRENGTHS (N/mm)	>60
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
WATER SOLVENT PROTECTED	No
ADDITIONAL INFORMATION	
TOP FACE	The top face is available in the buffed and cast (IR) version

DISTRIBUTED BY:

COMPANY NAME

Address

Address

Tel



www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions. disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.