



FOLIO / FOLIO UV

Description

Vulcan Folio has a special compressible layer (Vulcan DynaTech) to avoid shock marks and it is suitable for all kind of modern high speed sheet-fed presses.


The reduced gauge loss is a real advantage for high quality print jobs.

The sharp dot reproduction is the best that can be achieved thanks to its micro-buffed printing face.


MAIN APPLICATION

Commercial Sheetfed,
High Quality Packaging

Vulcan Folio/Folio UV is available in 3-ply, (1,96 mm) thickness.



Vulcan Folio



Vulcan Folio UV

The product at a glance

PRINTING SURFACE COLOUR	Dark Green/Purple
THICKNESS (mm)	1,96
SURFACE ROUGHNESS (Ra micron)	0,6/0,8
INK COMPATIBILITY	Hybrid/UV
ELONGATION (%)	<0,9
TENSILE STRENGTHS (N/mm)	>60
AVERAGE LOAD VALUE N/cm2 @ 0,23 mm Indentation	250
WATER SOLVENT PROTECTED	Yes
NEW TECHNOLOGIES	Dynatech
ADDITIONAL INFORMATION	
TOP FACE COMPOUND	Dedicated UV version available.
SPECIAL COMPRESSIBLE LAYER	Very special compressible layers with Dynatech technology for high quality printing.

DISTRIBUTED BY:
COMPANY NAME

Address
Address
Tel



www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions, disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.