



TECHNO

Description


VULCAN Techno has been developed to absorb the mechanical vibrations caused by new generation printing presses.

Vulcan Techno guarantees high level performance at high speed.


MAIN APPLICATION

Commercial Web

Vulcan Techno is available in 3-ply, (1,71 mm) thickness.



Standard



Vulcan Techno

✓ The product at a glance

PRINTING SURFACE COLOUR	Green
THICKNESS (mm)	1,71
SURFACE ROUGHNESS (Ra micron)	0,8
INK COMPATIBILITY	Hybrid
ELONGATION (%)	<0,9
TENSILE STRENGTHS (N/mm)	>60
AVERAGE LOAD VALUE N/cm² @ 0,23 mm Indentation	250
PAPER FEEDING	Positive
WATER SOLVENT PROTECTED	Yes
NEW TECHNOLOGIES	Dynatech
ADDITIONAL INFORMATION	
HYBRID TOP FACE COMPOUND	Conventional & Hybrid inks Print quality and durability Very special compressible layers
SPECIAL COMPRESSIBLE LAYER	Very special compressible layers with Dynatech technology designed to reduce shock marks.

DISTRIBUTED BY:

COMPANY NAME

Address

Address

Tel



www.trelleborg.com/printing

The information contained in this document is intended to provide guidance. The information is NOT a specification and all figures in the document are nominal. This document and the information it contains do not create any warranties for any product and Trelleborg Printing Solutions. disclaims any warranty of merchantability or fitness for a particular purpose for the product described in this document. This document discloses information that is proprietary to Trelleborg Printing Solutions. The receipt or possession of the document does not confer any right to reproduce or disclose the document, any information contained in it, or any physical article or device, or to practice any method or process except by written agreement with Trelleborg Printing Solutions. Trelleborg Printing Solutions is committed to the ongoing development of its products. For that reason, Trelleborg Printing Solutions reserves the right to alter the actual specifications of its products without prior notice.